



# Apaseal®

## A210

### FULLY AUTOMATIC TYRE CHANGER

Best Price  
€ 1.985  
£ 1.687



MADE IN ITALY

SPECIAL  
END OF YEAR  
PRICE OFFER

A210 + EM7240

only

€ 3.495

£ 2.995

## EM7240

### LATEST GENERATION BALANCER

Best Price  
€ 1.695  
£ 1.440



## A210

### technical data

Best Price  
€ 1.985  
£ 1.687



Best Price  
€ 1.695  
£ 1.440

Turntable	Inside clamping capacity	13" ± 23"
	Outside clamping capacity	10" ± 20"
	Maximum tyre diameter	960 mm (38")
	Maximum tyre width	305 mm (12")
	Rotation torque	1200 Nm
	Rotation speed	8 rpm
	Height above the ground	665 mm
	Maximum opening	320 mm
	Shoe force	15.500 N
	Working range	8" ± 24"
	Power supply	230/400V 3ph 0,75kW
	Operating pressure	10 bar
	Weight	250 kg
	Dimensions L x D x H	1060x1570x1730 mm

**Characteristics**  
 Pneumatically-operated tilting arm support column with high torsional rigidity, can be tilted in any working position • Sliding support s with interchangeable clamping centres • Higher cast clamps for improved rim clamping from inside and outside • Turntable with two pneumatic cylinders able to safely clamp any type of rim • Telescopic (hexagonal) horizontal arm for quicker positioning of the head in relation to the rim • Simultaneous PNEUMATIC LOCKING of the horizontal arm and head carrier vertical arm with automatic positioning of the latter to ideal working position • Bead breaker - pneumatic rotary presser ideal for ultra-low tyre and light alloy spot rims (on request).

**Balancing procedure**  
 • Dynamic balancing on both sides of the rim • 7 ALU programmes (5 statistical ALUs + 2 ALU P) • Motorcycle dynamic • Motorcycle ALU • Static • OPT flash • Hidden Weight in ALU P • Split Weight in motorcycle programmes • "Shift Planes" Programme in ALU P  
 • Display of the unbalance in grams or ounces • Automatic balancing with brake at the end of the electronic cycle

Balancing speed	90-130 rpm
Resolution	1 g (0.0353 oz)
Average cycle time	7 s
Shaft diameter	40 mm
Rim width setting range	1.5" to 20"
Rim diameter setting range	1" to 35"
Rim diameter measurable with the sensor	1" to 28"
Maximum wheel width (with guard)	600 mm (23.5")
Maximum wheel diameter (with guard)	1117 mm (44")
Maximum wheel/machine distance	275 mm (11")
Maximum wheel weight	75 kg
	- with fixing to the ground
	- with supporting foot
Supply voltage	100-115/200-230V 1ph
Maximum dimensions l x d x h (mm)	1195 x 583 x 1052



APASEAL LTD - Unit 4 Springhill Rd. Carrbane Ind Estate, Newry BT35 6EF  
 Tel No 028 302 62825 or 048 302 62825 - e-mail: info@apaseal.ie - Website: www.apaseal.ie



## EM7240

### technical data

